Print density

This document is built four times — once at `relaxed`, once at `normal`, once at `compact`, and once at `tight` — from the same source, on the same paper, with the same margins. The only thing that differs between the four PDFs is `pdf.density`, so anything you see change here is that setting and nothing else.

What to look at

The four values a density moves are the four that decide how many sheets a document comes out as. Each one is on this page:

- **Type size.** How large the body text is set. It is the first thing anyone notices and the last lever a density should reach for, because it also lengthens the line.
- **Leading.** The distance from one baseline to the next. A stylesheet written for a screen is generous here, and on paper that generosity is most of what the page count is paying for.
- **The space above headings.** Air that separates one section from the next. On screen it is scrolled past; on paper it is bought by the sheet.
- **Table cell padding.** Invisible until a document is largely tables, at which point it decides whether the table fits on one page or two.

Where the sheets come from

Between `relaxed` and `normal` the type size does not change at all. Both set the body at 16px; what changes is the leading, the space above headings, and the padding inside table cells. The document still comes out shorter, which is the point: a page set for reading on a screen is not merely a smaller page set for paper, and the difference is mostly air rather than type.

Below `normal` the type does get smaller, and something else follows it. The width of the text column is whatever `pdf.margin` leaves — a density does not narrow it — so every step down in type size is also a step up in the number of characters on each line. At the default A4 margins, 16px is roughly 42 Japanese characters to the line, and 12px is around 56. That is a real cost, and it is why the tighter presets are worth choosing deliberately rather than by default.

If you want the tighter type without the longer line, widen `pdf.margin` in the same change. The two settings are separate because the right measure depends on the script the document is written in, which is not something a preset can decide for you.

The presets

Preset	Type size	Leading	Above headings	Cell padding	Reads as
`relaxed`	16px	1.7	1.8em	0.5rem 0.8rem	The document as it is on screen
`normal`	16px	1.45	0.9em	0.35rem 0.6rem	The default: screen type, set for paper
`compact`	14px	1.35	0.8em	0.3rem 0.5rem	A report meant to be handed round
`tight`	12px	1.3	0.6em	0.2rem 0.35rem	An appendix nobody reads end to end

`relaxed` is the screen setting under a name. Because it is exactly what the stylesheet already does, asking for it writes no print rules at all — including none that would pin a font size on someone printing this HTML from their own browser.

Setting it

A name is usually enough:

```
pdf:
  pageSize: A4
  margin: { top: 20mm, right: 15mm, bottom: 20mm, left: 15mm }
  density: compact
```

When a preset is close but not right, give an object instead. `base` names the preset to start from and the object replaces only what it names, so changing one value does not mean copying the other three:

```
pdf:
  density:
    base: compact
    fontSize: 13px
    lineHeight: 1.4
```

A table, for the cell padding

Cell padding is the value that is easiest to overlook and hardest to ignore once a document is mostly tables. The rows below are here to make it visible.

Step	Owner	Due	State	Note
Collect the source documents	Documentation	Week 1	Done	Two of them were still in a wiki
Agree the section order	Documentation	Week 1	Done	Settled by the sidebar, not by the file names
Convert the tables	Engineering	Week 2	Done	The wide ones needed their columns rethought
Draw the diagrams	Engineering	Week 2	In progress	Mermaid, pre-rendered so the PDF needs no runtime
Check the fonts on the build machine	Engineering	Week 2	Done	`fontCheck` reports what is missing before the artifact is made
Set the print density	Documentation	Week 3	In progress	This document is the comparison
Decide the margins	Documentation	Week 3	Open	Depends on the density above
Read the whole thing on paper	Review	Week 3	Open	On the printer it will actually be printed on
Fix what the printing turned up	Documentation	Week 4	Open	There is always something
Add the page numbers to the footer	Engineering	Week 4	Done	Default footer; no configuration needed
Sign off the layout	Review	Week 4	Open	One signature, not four
Hand the PDF over	Documentation	Week 4	Open	With the source, so it can be rebuilt

Lists, for the leading

An ordered list runs through the same leading as the body text, so it shows the same difference:

1. Build the document at each density from the same source.
2. Print one sheet of each on the paper it will be read on, not on the screen.
3. Read the body text first, then the tables, then the headings.
4. Choose the loosest one that still fits the number of sheets you have.
5. Write the choice into `monodocs.config.yml` so the next build makes the same document.

The last step is the one that gets skipped. A density chosen once and left in the configuration is a document that keeps its shape; a density chosen at the printer is a document that changes shape every time somebody rebuilds it.

Generated by monodocs v0.19.0